



# masteroil ATF MB 15

## Description

masteroil ATF MB 15 is an HC synthetic lubricant based on carefully selected, very high-grade base oils and is intended for the latest MB 7-speed automatic transmissions (NAG2FE+). It impresses due to outstanding friction resistance, excellent performance and fuel efficiency.

## Application

masteroil ATF MB 15 is recommended for sports vehicles (NA G2FE+) and is not downwards compatible with the previous 5 and 7-speed transmissions requiring MB 236.10, 236.12, 236.14.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	17.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	4.4
Viscosity index	ASTM D2270	–	172
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa-S	3500
Flash point (COC)	ASTM D92	°C	178
Colour	Visual	–	Blue / blue

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

## Specifications

- Infiniti Matic-G
- MB 236.15
- Nissan Matic-G

## Advantages

Wear protection: Significantly extended transmission service life. Friction properties: Very quiet gear changes without vibrations.

Extended oil life: Excellent temperature and oxidation stability.

## Notes

masteroil ATF MB 15 is not suitable for use in DCT / DSG (dual clutch) transmissions or in CVTs (continuously variable transmissions).

## This product is available in the following container sizes:

- 1 litre
- 5 litres
- 30 litres
- 60 litres