



masteroil MTF SAE 75W-140

Description

This is a semi-synthetic lubricant based on carefully selected, highly refined base oils. It is a high-performance transmission fluid for all differential gears (also with differential lock) and is characterised by an extraordinarily high viscosity stability at different temperatures, not to mention very high flowability at low temperatures.

Application

This product is used in heavy-duty axles and reduction gears of cars, HGVs and off-road vehicles. The oil has limited slip properties and is especially recommended for 4x4 vehicles.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.893
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	170
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	26.5
Viscosity index	ASTM D2270	-	195
Pour point	ASTM D6892	°C	-51
Flash point (COC)	ASTM D92	°C	190

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- API GL-5
- BMW MSP/A / 83 22 1 470 080 / 83 22 2 282 583
- Ford WSS-M2C187-A
- Ford WSS-M2C192-A
- Ford WSS-M2C192A+/M2C118-A
- GM 1942386 / 12346140
- MIL L-2105 C / D

Advantages

Friction properties: Very smooth shifting, no vibrations

Wear protection: Extended transmission service life

Longer oil life: Excellent temperature and oxidation stability

This product is available in the following container sizes:

- 1 litre
- 30 litres
- 60 litres

