



masteroil ATF 8 H

Description

masteroil ATF 8 H is a fully synthetic lubricant based on carefully selected, very high-grade base oils and specifically developed for ZF automatic transmissions with 6, 8 and 9 gears. Its special formulation ensures problem-free operation and smooth shifting.

Application

masteroil ATF 8 H is primarily intended for ZF 6, 8 and 9-speed automatic transmissions used in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT vehicles.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	28.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	5.94
Viscosity index	ASTM D2270	-	164
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa-S	9500
Flash point (COC)	ASTM D92	°C	210
Colour	Visual		Green

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- BMW 83 22 2 289 720 / 83222152426 / ATF3+
- Chrysler 68157995AA
- Fiat 9.55550-AV5
- Jaguar 02JDE26444
- Land Rover LR023288
- MB 236.82
- VW G 060 162

Advantages

Wear protection: Significantly extended transmission service life. Friction properties: Very quiet gear changes without vibrations.

Extended oil life: Excellent temperature and oxidation stability.

Notes

masteroil ATF 8 H is not suitable for use in DCT / DSG (dual clutch) transmissions or in CVTs (continuously variable transmissions).

This product is available in the following container sizes:

- 1 litre
- 5 litres
- 30 litres
- 60 litres