



masteroil ATF Life Protect 6

Description

This is an HC synthetic lubricant based on carefully selected, very high-grade base oils and specifically developed for ZF automatic transmissions with 6 gears. Its special formulation ensures problem-free operation and smooth shifting.

Application

The oil is primarily intended for ZF 6-speed automatic transmissions used in BMW, Jaguar and Land Rover vehicles. However, it is also suitable for models from other manufacturers that recommend an oil of this type (e.g. Audi Quattro).

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	31.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.17
Viscosity index	ASTM D2270	-	152
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa-S	9500
Flash point (COC)	ASTM D92	°C	202
Colour	VISUAL		AMBER

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

Specifications

- AML 4G4319A509/AA/S
- Bentley PY112995PA
- BMW 83220142516 / M-1375.4 / ATF 2 / 83 22 2 305 396
- Hyundai 040000C90SG
- Jaguar Fluid 8432
- Land Rover TYK500050
- Maserati 231603
- VW G 055 005
- ZF TE-ML 11

Advantages

Wear protection: Significantly extended transmission service life

Friction properties: Very quiet gear changes without vibrations

Extended oil life: Excellent temperature and oxidation stability

This product is available in the following container sizes:

- 1 litres
- 5 litres
- 30 litres
- 60 litres