



# masteroil ATF MB 14

## Description

masteroil ATF MB 14 is an HC synthetic lubricant based on carefully selected, very high-grade base oils and mainly intended for all MB 7-speed automatic transmissions, as well as for transmissions of the type NAG-V Sport. The product impresses due to excellent friction resistance and outstanding performance.

## Application

It is recommended for the Mercedes-Benz 7G-Tronic and 5-speed automatic transmission. Due to its special composition and particular properties, it is not suitable for other applications.

Typical characteristic values Property	Method	Unit	Value
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	28.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	5.9
Viscosity index	ASTM D2270	–	154
Brookfield viscosity at -40°C	ASTM 2983	mPa·S	11800
Flash point (COC)	ASTM D92	°C	206
Pour point	ASTM D6892	°C	-45
Colour	Visual	–	Red / red

We reserve the right to change our products' general properties so that our customers can always benefit from the latest technical developments.

## Specifications

- MB 236.14

## Advantages

Wear protection: Significantly extended transmission service life. Friction properties: Very quiet gear changes without vibrations.

Extended oil life: Excellent temperature and oxidation stability.

## Notes

masteroil ATF MB 14 is not suitable for use in DCT / DSG (dual clutch) transmissions or in CVTs (continuously variable transmissions).

## This product is available in the following container sizes:

- 1 litre
- 5 litres
- 30 litres
- 60 litres